





## **STAY FLEXIBLE...**

The RAPTOR 300 is the chameleon of the mulching carriers that provides unparalleled customization possibilities to answer the individual requirements of each end user. The modular design, in combination with various options, allow multiple configurations. Accessibility and the compact architecture make this unit stand out when speaking of ergonomy & efficiency. Featuring the latest technology and heavy-duty components, the RAPTOR 300 sets new standards in the mulching industry.



2

をないたたちのうないとなった

3

The mechanical drive generates important fuel savings and improves efficiency compared to hydraulically-driven mulchers.





нШI

As with all of PRINOTH's products, reliability and durability are the top priorities.

日本にない、たいのの



RAPIOS SOO

R

Mobility, transportability and attachments possibilities add up to qualify the RAPTOR 300 as one of the most versatile units on the market. のためのでも



We emphasize on safety features for operator and vehicle. All models from the RAPTOR series line-up benefit from the same highly-certified safety systems.









# TECHNICAL HIGHLIGHTS

#### UNDERCARRIAGE – DELTA TRACKS »

- improved robustness
- » better self-cleaning effec
- » better off-road mobility

The shape of the undercarriage protects the vehicle in case of barriers like stumps and rocks and simplifies backwards operations.

#### PTO DRIVE »

- adaptive to all attachments
- » direct drive efficiency
- » robust and reliable

The RAPTOR 300 becomes a multi-purpose machine as attachments can be easily switched according to the type of work to be done.

#### **POWERBELT DRIVE »**

- » robust and reliable
- » direct-drive efficiency
- » increased range of lifting

The durable and low-maintenance PowerBelt drive has a lifting height limit that is unique to a mechanically-driven head.

#### ACCESSIBILITY »

- » tilting cab
- » service friendly architecture
- » five full-access doors

All components that require maintenance or monitoring are located near the service doors and can be easily reached.









... BE SAFE

#### CAB

- » Customize
- » Ergonomio
- » Comfortabl

Best in class cab for safe and productive operation.





## TIER 4 FINAL/STAGE 4

••••••	······
Engine	CAT C7.1
Power	275 HP
Displacement	7 l
Max. torque	1257 Nm
Tank	360 l (95 gal)
Urea tank (AdBlue)	26 l (6.8 gal)
Voltage	24 V
Hydraulic tank	62 l

## UNDERCARRIAGE

#### 7.5 km/h (4.6 mph) Max. speed Undercarriage type D4 one blade/dual blade Grouser shoes Grouser Width Gauge (mm/in) (mm/in) (mm/in) (1600/63) 600/23.5 2200/86.5 730/28.7 2500/98.5 (1750/69)

.....

TIER 3/	'STAGE	3A
---------	--------	----

	••••••	•••••••
7.1	Engine	CAT C7.1
ΗP	Power	275 HP
7 l	Displacement	7 l
lm	Max. torque	1030 Nm
al)	Tank	360 l (95 gal)
al)		
v	Voltage	24 V
21	Hydraulic tank	62 l

### WEIGHT AND MOBILITY

15250 kg (33620 lb) 12400 kg (27337 lb)
340 g/cm² (4.8 PSI) 280 g/cm² (4.0 PSI)
30° 45°


.....


## ATTACHMENTS


•••••••••••••••••••••••••••••••••••••••	•••••••••••••••••••••••••••••••••••••••
PTO:	
M550 m	2200 kg (4850 lb)
M650 m	2850 kg (6280 lb)
RF800 m	3500 kg (7716 lb)
All other 3-point-hitch at	tachments
PowerBelt:	
M650 m	2750 kg (6060 lb)

OPTIONS

Winch	l							
Press	urized	cab						
Fire s	upress	ion sy	stem					
Arctio	packa	age						
GPS								
Hitch								
Addit	ional r	oll ba	r pro	tecti	on			
Coola	nt hea	ting s	ystei	n				
Locki	ng sys	tem fo	or tra	cks				
Centr	al lubr	icatio	n sys	tem				
Addit	ional I	iydrau	lic ci	ircuit				
etc.								







## **TECHNICAL DATA**





Other sales and service sites can be found on www.prinoth.com

AHWI Maschinenbau GmbH Im Branden 15 D-88634 Herdwangen Phone: +49 (0)7557 9212-0 Fax: +49 (0)7557 9212-92 ahwi@prinoth.com PRINOTH AG Brennerstraße 34 I-39049 Sterzing (BZ) Phone: +39 0472 72 26 22 Fax: +39 0472 72 26 18 prinoth@prinoth.com PRINOTH Ltd. (Canada) North American Headquarters 1001, J.-A.-Bombardier Street Granby (Quebec) J2J 1E9, Phone: +1.450.776.3600 Fax: +1.450.776.3685 prinoth.canada@prinoth.com